



Egalsoft®

6,5mm



Self-adhesive Carpet Underlay

- Very good leveling ability
- High compressive strength
- Extends the life of the carpet
- Increases the comfort and feeling of luxury
- Removable system without damaging the base floor

Technical information

Dimensional stability Traction		: 40 N/mm ² / length 256N / width 58N
Dimensional stability extension:	(test method: ISO 13934-1)	: 10% / length 24,2% / width 58,8%
Caster chair test	(Test method: EN 985)	: Suitable, double stick only
Impact sound reduction	(Test method: NA)	: ΔLw = 27 dB
Thermal resistance	(Test method: NA)	: 2,2 togs - 0,22m ² K/W
Fire retardency	(Test methode: EN ISO 9239-1)	: Efl
ASTM radial panel test	(Test methode: ASTM E 648-06)	: NA
Russian requirements on fire safety	(Test methode: FZ-123)	: NA



Installation instructions:

- Let the carpet as well as the underpadding acclimatise for 24 hours in the original packing in the room to be installed.
- The best temperature for installation is 5-20° C. and a humidity of 50-70%.
- make sure that the underfloor is absolutely dry and free of grit and dust.
- To cut the underpadding we recommend to use a trapezium blade.
- Underpadding can not prevent the natural shrinkage of carpet. For that reason we strongly advise always to use the double stick method (gluing both the underpadding as well as the carpet) in case of shrink-sensible qualities. Always follow the installation instructions of the carpet Manufacturer.