

TECHNICAL SPECIFICATION



Gerbur Aqua-Click Exotic collection brings the natural look of real stone flooring with none of the disadvantages. The many benefits are as follows:

Thickness (mm)		4.00
Wear Layer (mm)		0.3
Utilization Class		
Coating		PU with DiamondShield™
Embossing		Real Wood Texture
Bevelled		V-grooved
Fiberglass		yes
Installation Method		Floating floor installation
Plank Size		152.4mm x 1219.2mm
Sqm Per Pack		1.858
Pallet Packing		156.072 / 84 packs
Impact Sound Insulation	ISO 717-2	5 dB
Chemical Resistance	EN423	High Resistance
Residual Indentation	EN433	≤ 0.08mm
Dimensional Stability	EN434	≤ 0.08%
Colour Fastness to Light	EN20105-B02	≥ 6
Slip Resistance	DIN51130	R10
Water Resistance	EN13553	100% Water Proof
Abrasion Resistance	EN660-2	Group T
Antimicrobial Activity	ASTMG 21-96	Class 0
Fire Rating	EN ISO 9239-1	Bfl - S1
Warranty for Domestic use		Lifetime
Warranty for Commercial use		10 Years

Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards.



EMBOSSING : Registered Emboss Real Wood Structure. Thickness: 4mm. Wear Layer: 0.3mm. Coating: PU with DiamondShield™. Utilization Class: 33/42 Heavy Commercial. Produced with 100% virgin PVC. Satisfies Green Building Standards and earns LEED certification points in Commercial Applications. Gerbur Aqua Click Exotic Collection can be completely recycled. Installation: Installed as a Floating Floor. No Underlay or Glue Required.



INHERENT SAFETY FEATURES: Conforms to all regulatory requirements of commercial flammability codes, slip resistant requirements, certified for low VOC emissions for safer indoor air quality and host of other safety codes.

ECO- FRIENDLY : Gerbur luxury vinyl tile products are made with natural, environmentally friendly sustainable materials which are 100% recyclable.