





















## TECHNICAL SPECIFICATION

The floor covering selected belongs to the Gerbur Allure Tile family of luxury vinyl tiles (LVT), manufactured from several layers that have been laminated together, and commonly incorporating a printed film design layer. Planks should be installed using Gerbur recommended adhesives.

	DESCRIPTION	STANDARDS	RESULT
	Size	915mm x 101mm	
	Package	24 pcs per carton = 2.218m <sup>2</sup>	
	Finish	Registered Emboss, Matt Finish	
	Size	915mm x 152mm	
	Package	24 pcs per carton = 3.34m <sup>2</sup>	
	Thickness	3mm	
	Wear layer	0.55mm	
	Warranty	Commercial 10 Years* Domestic 15 Years*	
	Bevelled edge	yes	
	Standards	EN 649 ASTM F-1700	
	Classification	EN 685:42 Light industrial general EN 685:33 Commercial heavy EN 685:23 Domestic heavy ASTM F1700 Class 3 Type B	
	Reaction to fire	EN 13501-1 ISO 9239-1 ISO 11925-2 ASTM E-648-06 Class 1	Bfl-S1 Pass Pass
	Slip resistance	EN 13893 DIN 51130 BS 7976 AS/NZS 4586 ASTM C-1028	DS
	Staining resistance	EN 423 ASTM F-925	Class 0 Pass
	Light fastness	SO 105-B02 ASTM F-1515	> 6 > 7
	Abrasion resistance	EN 660-2 ASTM 3884	Group T Pass
	Dimensional stability EN 434	Δ 0.25% ASTM F-2199	Pass
	Acoustic impact noise reduction	EN ISO 717-2 EN ISO 140-8	ΔLm= 4 db
	Electrical behaviour body voltage	EN 1815	Pass
	Indentation – residual	EN 433 ASTM F-1914	Δ 0.1mm < 8%
	Castor chair continuous use	EN 425	Pass
	Thermal conductivity Suitable for underfloor heating	ISO 8302	0.0147m <sup>2</sup> K/W
	Adhesive	Acrylic Epoxy HT [High Temperature] PS [Pressure Sensitive]	Yes Yes Yes Yes
	Recycling		Suitable

\*Subject to terms

